

**ADDENDUM NO. 1
TO SPEC. 03-310
FOR 35,000 GVWR CONVENTIONAL CHASSIS
WITH 24 FOOT VAN BODIES**

Addendum No. 1 to Specification #03-310, for two (2) 35,000 GVWR Conventional Chassis with 24 Foot Van Bodies, bids to be opened on Wednesday, December 31, 2003 at 12:00 noon.

Please note the following Addition to the specifications:

Change Section 6 to include the following information for Front and Rear Axle Suspension. Delete Section 6 in it's entirety and replace with the attached addendum.

Meets Specs.

Yes No

- | | |
|-----|--|
| 6. | Front Axle and Suspension & Rear Axle and Suspension |
| | Front Axle |
| ___ | 6.1 Meritor MFS-12-143A Front Axle @ 12,000 |
| ___ | 6.1.1 State if different_____ |
| ___ | 6.2 Meritor 16.5 x 5 "Q+" cast spdr cam front brakes, double anchor, fab shoes |
| ___ | 6.3 Non-Asbestos front brake lining |
| ___ | 6.4 Conmet cast iron front brake drums |
| ___ | 6.5 Front brake dust shields |
| ___ | 6.6 Chicago rawhide Scotseal front-oil seals |
| ___ | 6.7 Standard spindle nuts for all axles |
| ___ | 6.8 Meritor automatic front slack adjusters |
| ___ | 6.9 TRW THP 60 power steering |
| ___ | 6.10 Power steering pump |
| ___ | 6.11 Two-quart see-through power steering reservoir |
| ___ | 6.12 12,000 lb. taper-leaf front suspension |
| ___ | 6.13 Maintenance-free, rubber bushings, front suspension |
| ___ | 6.14 Front shock absorbers |
| | Rear Axle and Suspension |
| ___ | 6.15 Meritor RS-23-160 R-SRS single rear axle at 23,000 lbs. |
| ___ | 6.15.1 State if different_____ |

Meets Specs

<u>Yes</u>	<u>No</u>		
___	___	6.16	5.63 Axle ratio
		6.16.1	State if different_____
___	___	16.17	Iron rear axle carrier housing
___	___	16.18	176T Meritor main drive-line w/half round yokes
		6.18.1	State if different_____
___	___	6.19	Driver controlled traction differential single rear axle
___	___	6.20	One (1) differential lok control valve
___	___	6.21	Blinking lamp w/each mode, SW, Diff Unlock W/ignition off, active <5 mph, deactivate >25 mph
___	___	6.22	Castrol Transynd Synthetic auto transmission oil and Mobile Synthetic 75W-90W all axles
___	___	6.23	Meritor 16.5 X 7 Q+ cast spider cam rear brakes, double anchor, fab'd shoes
		6.24.1	State if different_____
___	___	6.24	Non-asbestos rear brake lining
___	___	6.25	Cam brake auxiliary support brackets
___	___	6.26	Conmet cast iron rear brake drums
		6.27.1	State if different_____
___	___	6.27	Rear brake dust shields
___	___	6.28	Chicago rawhide Scotseal rear oil seals
___	___	6.29	Haldex long stroke one-drive axle spring parking chambers
		6.15.1	State if different_____
___	___	6.30	Meritor automatic rear slack adjustors
		6.16.1	State if different_____
___	___	6.31	Airliner 23,000 # rear suspension
___	___	6.32	Airliner ride height-high
___	___	6.33	Manual dump valve for air suspension with indicator light, w/o gauge, with buzzer
___	___	6.34	Rear air suspension dump valve auto-fill with ignition off or >5mph
___	___	6.35	Single air rear suspension leveling valve
___	___	6.36	Transverse control rods
___	___	6.37	Rear shock absorbers-one axle (air ride suspension)

All other terms and conditions to remain unchanged.

Dated this 12th day of December, 2003.

Purchasing Department

Tom Kopplin
Assistant Purchasing Agent